


Features

- Epitaxial planar die construction
- Built-in biasing resistors, $R_1 = R_2$

HF

Mechanical Data

- Case: SOT-363
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



SOT-363

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
UNM1N	SOT-363	3000 pcs / Tape & Reel	XC

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Breakdown Voltage	V_{CBO}	50	V
Collector-Emitter Breakdown Voltage	V_{CEO}	50	V
Emitter-Base Breakdown Voltage	V_{EBO}	10	V
Collector Current (Continuous)	I_C	100	mA




Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	200	mW
Operating Junction Temperature Range	T_J	-55 ~ +150	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 ~ +150	$^\circ\text{C}$


Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector Cut-off Current	I_{CBO}	$V_{CB} = 50\text{V}, I_E = 0$	-	-	0.1	μA
Collector Cut-off Current	I_{CEO}	$V_{CE} = 50\text{V}, I_B = 0$	-	-	0.5	μA
Emitter Cut-off Current	I_{EBO}	$V_{EB} = 10\text{V}, I_C = 0$	-	-	0.33	mA
DC Current Gain	h_{FE}	$V_{CE} = 5\text{V}, I_C = 10\text{mA}$	70	-	-	-
Collector-emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 5\text{mA}, I_B = 0.25\text{mA}$	-	-	0.3	V
Input voltage	$V_{I(ON)}$	$V_{CE} = 0.2\text{V}, I_C = 5\text{mA}$	1.3	-	3	V
Input voltage	$V_{I(OFF)}$	$V_{CE} = 5\text{V}, I_C = 0.1\text{mA}$	1	-	1.5	V
Transition Frequency	f_T	$V_{CE} = 10\text{V}, I_C = 5\text{mA}$	-	250	-	MHz
Output Capacitance	C_{ob}	$V_{CB} = 10\text{V}, I_E = I_C = 0$ $f = 1\text{MHz}$	-	-	6	pF
Input Resistor	R_1		15.4	22	28.6	$\text{k}\Omega$
Resistance ratio	R_1/R_2		0.9	1.0	1.1	-

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Package Outline Dimensions (Unit: mm)



SOT-363		
Dimension	Min.	Max.
A	2.00	2.20
B	1.15	1.35
C	0.85	1.05
D	0.15	0.35
E	0.25	0.40
G	0.60	0.70
H	0.02	0.10
J	0.05	0.15
K	2.20	2.40

Mounting Pad Layout (Unit: mm)

SOT-363



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.